

15

14

13

12

11

10

9

8

7

6

5






4

3



2

1


料号 Material No	类别 Category	材质 The material		数量/pcs The number of pcs
C3004H-1*5P	HOUSING	Base	Nylon 66 UL 94V-0 (Black)	1000pcs/包




Poles	Part NO.		Dimensions mm	
	A	B	A	B
2	C3004H-1X2P	MX3.0-1X2P	3.00	8.20
3	C3004H-1X3P	MX3.0-1X3P	6.00	9.90
4	C3004H-1X4P	MX3.0-1X4P	9.00	12.90
5	C3004H-1X5P	MX3.0-1X5P	12.00	15.90
6	C3004H-1X6P	MX3.0-1X6P	15.00	18.90




1x2




1x3



1x4



1x5



1x6

### 规格 Specifications

- ◆1、极数 Poles: 1X2P/1X6P to 2X1P/2X12P
- ◆2、额定电流 Current rating: 5.0A AC, DC
- ◆3、额定电压 Voltage rating: 250V AC, DC
- ◆4、温度范围 Temperature range: -25°C to +85°C
- ◆5、接触电阻 Contact resistance: ≤15mΩ
- ◆6、绝缘电阻 Insulation resistance: ≥1000mΩ
- ◆7、耐电压 Withstand voltage: 1500V AC/minute
- ◆8、适用线规 Applicable wire: AWG #30 to #20
- ◆9、适用基板厚度 (Applicable PC board thickness):  
1.6mm to 2.0mm

未注公差				HWT 广州市恒炜电子有限公司 GuangZhou HengWei Electronic Co., Ltd					
>0-3	>3-18	>18-50	>50-120	单位	比例	Design Units	SIZE	页码	
±0.12	±0.15	±0.3	±0.5	MM Only	—	METRIC	A4		
制作	审核	批准	材料	图号	Part No				
姚灿瑜	陈小波	王日和	见图解	品名	MX3.0 (3004H) -1 × 5P 公壳				

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1