






| | | | |
|------------------|----------------|---------------------------|-----------|
| 料号 Materia No | 类别 Category | 材质 The material | 数量/pcs |
| C3003H-2*3P有耳 | Housing | Nylon 66 UL 94V-0 (Black) | 1000pcs/包 |



| Poles | Part NO. | | Dimensions mm | |
|-------|--------------|-------------|---------------|-------|
| | | | A | B |
| 2 | C3003H-2*1P | MX3.0H2×1P | -- | 5.60 |
| 4 | C3003H-2*2P | MX3.0H2×2P | 3.00 | 8.60 |
| 6 | C3003H-2*3P | MX3.0H2×3P | 6.00 | 11.60 |
| 8 | C3003H-2*4P | MX3.0H2×4P | 9.00 | 14.60 |
| 10 | C3003H-2*5P | MX3.0H2×5P | 12.00 | 17.60 |
| 12 | C3003H-2*6P | MX3.0H2×6P | 15.00 | 20.60 |
| 14 | C3003H-2*7P | MX3.0H2×7P | 18.00 | 23.60 |
| 16 | C3003H-2*8P | MX3.0H2×8P | 21.00 | 26.60 |
| 18 | C3003H-2*9P | MX3.0H2×9P | 24.00 | 29.60 |
| 20 | C3003H-2*10P | MX3.0H2×10P | 27.00 | 32.60 |
| 22 | C3003H-2*11P | MX3.0H2×11P | 30.00 | 35.60 |
| 24 | C3003H-2*12P | MX3.0H2×12P | 33.00 | 38.60 |

规格 Specifications

- ◆1、极数 Poles: 1X2P/1X6P to 2X1P/2X12P
- ◆2、额定电流 Current rating: 5.0A AC, DC
- ◆3、额定电压 Voltage rating: 250V AC, DC
- ◆4、温度范围 Temperature range: -25°C to +85°C
- ◆5、接触电阻 Contact resistance: ≤15mΩ
- ◆6、绝缘电阻 Insulation resistance: ≥1000mΩ
- ◆7、耐电压 Withstand voltage: 1500V AC/minute
- ◆8、适用线规 Applicable wire: AWG #30 to #20
- ◆9、适用基板厚度 (Applicable PC board thickness): 1.6mm to 2.0mm

| | | | | | | | | | |
|-------|-------|--------|---------|--|------------------------|--------------|------|---------|--|
| 未注公差 | | | | HWT 广州市恒炜电子有限公司 GuangZhou HengWei Electronic Co., Ltd | | | | | |
| >0-3 | >3-18 | >18-50 | >50-120 | 单位 | 比例 | Design Units | SIZE | 页码 | |
| ±0.12 | ±0.15 | ±0.3 | ±0.5 | MM Only | — | METRIC | A4 | Part No | |
| 制作 | 审核 | 批准 | 材料 | 图号 | | | | | |
| 姚灿瑜 | 陈小波 | 王日和 | 见图解 | 品名 | MX3.0 (C3003H) -2×3P有耳 | | | | |