



规格 Specifications

- ◆1、极数 Poles: 1X2P/1X5P to 2X1P/2X12P
- ◆2、额定电流 Current rating: 9.0A AC, DC
- ◆3、额定电压 Voltage rating: 250V AC, DC
- ◆4、温度范围 Temperature range: -25°C to +85°C
- ◆5、接触电阻 Contact resistance: $\leq 10\text{m}\Omega$
- ◆6、绝缘电阻 Insulation resistance: $\geq 1000\text{m}\Omega$
- ◆7、耐电压 Withstand voltage: 1500V AC/minute
- ◆8、适用线规 Applicable wire: AWG #16 to #30
- ◆9、适用基板厚度 (Applicable PC board thickness): 0.8mm to 2.0mm

| 未注公差 | | | | HWT 广州市恒炜电子有限公司 GuangZhou HengWei Electronic Co., Ltd | | | | | |
|-------|-------|--------|---------|--|------------------|--------------|------|----|--|
| >0-3 | >3-18 | >18-50 | >50-120 | 单位 | 比例 | Design Units | SIZE | 页码 | |
| ±0.12 | ±0.15 | ±0.3 | ±0.5 | MM Only | — | METRIC | A4 | | |
| 制作 | 审核 | 批准 | 材料 | 图号 | Part No | | | | |
| 温静斐 | 陈小波 | 王日和 | 见图解 | 品名 | 5557T/C4202T母端高脚 | | | | |

15 14 13 12 11 10 9 8 7 6 5 4 3 2 1